

Solar controller MPPT 100/30A - Victron

Battery voltage	12 V
Max charge current	30 A
Absorption voltage	14,60V
Voltage Float	13,80V
Equalization time	Deactivated
Re-Bulk Voltage Offset	No need to modify
Absorption time	Adaptive
Maximum absorption time	Maximum (24 h)
Tail current (in amperes)	Deactivated
Percentage of equalization current	X
Automatic equalization	Deactivated
Equalization stop mode	X
Maximum equalization time	X
Manual equalization	Never on
Temperature compensation	Deactivated
Low temperature cut-out	0°C
Load output	Always on
Port_Tx	Normal communication

Solar controller MPPT 100/50A - Victron

Battery voltage	12 V
Max charge current	50 A
Absorption voltage	14,60V
Voltage Float	13,80V
Equalization time	Deactivated
Re-Bulk Voltage Offset	No need to modify
Absorption time	Adaptive
Maximum absorption time	Maximum (24 h)
Tail current (in amperes)	Deactivated
Percentage of equalization current	X
Automatic equalization	Deactivated
Equalization stop mode	X
Maximum equalization time	X
Manual equalization	Never on
Temperature compensation	Deactivated
Low temperature cut-out	0°C
Load output	Always on
Port_Tx	Normal communication